




# COMPETITOR COLLECTION

## Triple Tier Locker

Date Issued: 10-11



		HEIGHT WITH LEGS	
WIDTH	DEPTH	66	78
12	12		
12	15		
12	18		
15	15		
15	18		

		HEIGHT WITHOUT LEGS	
WIDTH	DEPTH	66	72
12	12		
12	15		
12	18		
15	15		

NOTE: Top diamond perforations on 72"/78" height only

THIS MANUFACTURER RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN OR DIMENSIONS WITHOUT FORMAL NOTICE





ASI Storage Solutions

## COMPETITOR COLLECTION

# Triple Tier Locker

Date Issued: 10-11

### SPECIFICATION

**Material** – All major steel parts shall be of mild cold rolled commercial quality steel.

**Finish** – All material shall be power washed and phosphate treated for maximum finish color adhesion. All components shall be finished with a hybrid epoxy/polyester powder, electrostatically applied to ensure uniform thickness and baked to cure.

**Construction** – All lockers shall be built on a unit principle with common intermediate uprights separating units.

**Door Frames** – Shall be 16 gauge formed in a channel shape. Vertical members shall have additional flange to provide a continuous door strike. Cross frame members shall also be 16 gauge channel shaped, including intermediate cross frames.

**Doors** – Shall be 14 gauge, channel shaped on both the lock and hinge side, with angle formations across the top and bottom. Locker doors shall have a 16 gauge full height reinforcement channel.

**Body** – Backs shall be 18 gauge; all other body parts shall be 16 gauge. Bolt spacing shall not exceed 9" o.c.

**Hinges** – Shall be full length 16 gauge continuous piano type riveted to both door and frame.

**Handles** – Shall be one-piece 20 gauge deep drawn stainless steel cup designed to accommodate locks.

**Latching** – Lockers shall have an 11 gauge frame hook with anti pry feature secured to the frame. The frame hook shall have a padlock hasp protruding through the recessed handle. A rubber silencer shall be firmly secured to the frame.

**Interior Equipment** – Locker shall have three wall hooks per tier.

**Number Plates** – Each locker shall have a polished aluminum number plate riveted to door frame with black numerals 3/8" high.

**Color** – Doors, Frames and all body parts shall be finished in same color.

**Assembly** – Factory assembled lockers shall be riveted. Knocked Down "KD" lockers shall be supplied with nuts and bolts unless otherwise specified.

**Installation** – Lockers shall be installed in accordance with ASI Storage Solution's installation instructions and shall be level and plumb with flush surfaces and rigid attachment to anchoring surfaces.